

MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS - WARNE MFG. COMPANY QD GRL RUGER #1, BLACKHAWK, MINI 14 RINGS 1 INCH HIGH MATTE

Quickly Removable QD

Maxima Grooved Receiver Line of scope mounts are designed to fill the need of mounting scopes to rifles with an integrated receiver mounting rail. Because each manufacturer has their own proprietary mounting rail design, each ring model must be machined to exacting tolerances for proper fit and function. The Maxima Grooved Receiver line fulfills that need. The precision CNC machined Warne rings provide unsurpassed strength, durability and quality, and fit a variety of rifle models including Ruger #1, Ruger 77, Mini 14 & 30, and Ruger Blackhawk and Redhawk. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place.



Attributes

- Name: WARNE MFG. COMPANY QD GRL RUGER #1, BLACKHAWK, MINI 14 RINGS 1 INCH HIGH MATTE
- Manufacturer: WARNE MFG. COMPANY
- Product no.: 947000052
- Mfr. No.: 2RLM
- Finish: Matte Blue
- Height: .585"
- Scope Tube Diameter: 1"
- Size: High
- Style: Quick-Release Rings
- Delivery weight: 0.227kg
- UPC: 656813010868

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS Safety Instruction Guide](#)
- [Český: MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS Bezpečnostní pokyny](#)

MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS Safety Instruction Guide

Introduction

Thank you for choosing the MAXIMA Grooved Receiver Line Quick Detach Ruger Rings by Warne MFG. Company. This product is designed to provide a secure and reliable method for mounting optics on rifles with integrated receiver mounting rails. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that the rings are compatible with your specific rifle model before use.
- Always inspect the rings for any signs of damage or wear before installation.
- Follow all instructions provided in this guide for proper installation and usage.
- Store the rings in a cool, dry place to avoid deterioration.
- Keep the product out of reach of children and vulnerable individuals.

Specific Safety Precautions for Use

- Ensure that the scope is securely mounted to prevent it from becoming dislodged during use.
- Do not exceed the recommended torque specifications when tightening the rings to the rifle.
- Avoid using the rings in extreme conditions (e.g., excessive heat, moisture) that may compromise their integrity.
- Be cautious when adjusting the indexable lever to prevent pinching fingers or causing injury.
- Regularly check the mounting to ensure that it remains secure and does not loosen over time.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench and appropriate screwdriver.
- Ensure that the rifle is unloaded and pointed in a safe direction during installation.

2. Installation:

- Align the rings with the integrated mounting rail on your rifle.
- Place the rings onto the rail, ensuring they are positioned correctly for your scope.
- Securely tighten the screws on the rings using the torque wrench to the manufacturer's recommended specifications.
- After tightening, check that the rings are firmly attached and do not move.

3. Mounting the Scope:

- Place the scope into the rings and adjust its position as desired.
- Tighten the scope rings to secure the scope in place, ensuring it is level and aligned with the rifle.

4. Using the Indexable Lever:

- To detach the scope, pull out on the lever and turn it to the desired position.
- Ensure that the lever snaps back into place securely after reattachment.

5. Final Check:

- Once installed, perform a final inspection to confirm that all components are securely fastened and that the scope is properly aligned.
- Test the setup by gently shaking the rifle to ensure stability.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste. Instead, consider recycling options where available.

Contact Information for Further Support

For any questions or concerns regarding the MAXIMA Grooved Receiver Line Quick Detach Ruger Rings, please refer to the manufacturer's website or contact their customer support for assistance.

Thank you for your attention to these safety instructions. Enjoy your experience with the MAXIMA Grooved Receiver Line Quick Detach Ruger Rings, and always prioritize safety while using your firearm.

MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS Bezpečnostní pokyny

Úvod

Děkujeme, že jste si vybrali MAXIMA Grooved Receiver Line Quick Detach Ruger Rings od společnosti Warne MFG. Tento produkt je navržen tak, aby poskytoval bezpečný a spolehlivý způsob montáže optiky na pušky s integrovanými montážními lištami. Prosím, pečlivě si přečtěte tuto příručku k bezpečnosti, abyste zajistili bezpečné a efektivní použití produktu.

Obecné bezpečnostní pokyny

- Ujistěte se, že kroužky jsou kompatibilní s vaším konkrétním modelem pušky před použitím.
- Vždy zkontrolujte kroužky na jakékoli známky poškození nebo opotřebení před instalací.
- Dodržujte všechny pokyny uvedené v této příručce pro správnou instalaci a použití.
- Ukládejte kroužky na chladném a suchém místě, aby se předešlo poškození.
- Držte produkt mimo dosah dětí a zranitelných osob.

Specifické bezpečnostní opatření pro použití

- Ujistěte se, že optika je bezpečně namontována, aby se předešlo jejímu uvolnění během použití.
- Nepřekračujte doporučené hodnoty utahovacího momentu při utažení kroužků na pušku.
- Vyhněte se používání kroužků v extrémních podmínkách (např. nadměrné teplo, vlhkost), které by mohly ohrozit jejich integritu.
- Budte opatrní při nastavování indexovatelné páčky, abyste se vyhnuli zkrřížení prstů nebo způsobení zranění.
- Pravidelně kontrolujte montáž, aby se zajistilo, že zůstává bezpečná a nevolní se v průběhu času.

Pokyny pro instalaci a použití

1. Příprava:

- Shromážděte všechny potřebné nástroje, včetně momentového klíče a vhodného šroubováku.
- Ujistěte se, že je puška vybitá a namířená bezpečným směrem během instalace.

2. Instalace:

- Zarovnejte kroužky s integrovanou montážní lištou na vaší pušce.
- Umístěte kroužky na lištu a ujistěte se, že jsou správně umístěny pro vaši optiku.
- Bezpečně utáhněte šrouby na kroužcích pomocí momentového klíče podle doporučených specifikací výrobce.
- Po utažení zkontrolujte, že jsou kroužky pevně připevněny a nehýbou se.

3. Montáž optiky:

- Umístěte optiku do kroužků a upravte její pozici podle potřeby.
- Utáhněte kroužky optiky, abyste zajistili optiku na místě, ujistěte se, že je vodorovná a zarovnaná s puškou.

4. Použití indexovatelné páčky:

- Chcete-li odpojit optiku, vytáhněte páčku a otočte ji na požadovanou pozici.
- Ujistěte se, že se páčka po opětovném připojení bezpečně zaklapne na místo.

5. Konečná kontrola:

- Po instalaci proveďte konečnou kontrolu, abyste potvrdili, že všechny komponenty jsou bezpečně utaženy a že optika je správně zarovnaná.
- Otestujte nastavení jemným zatřesením puškou, abyste zajistili stabilitu.

Pokyny pro likvidaci

- Likvidujte produkt v souladu s místními předpisy.
- Nevyhazujte produkt do domácího odpadu. Místo toho zvažte možnosti recyklace, kde jsou k dispozici.

Kontaktní informace pro další podporu

Pro jakékoli dotazy nebo obavy týkající se MAXIMA Grooved Receiver Line Quick Detach Ruger Rings se prosím obraťte na webové stránky výrobce nebo kontaktujte jejich zákaznickou podporu pro pomoc.

Děkujeme za vaši pozornost k těmto bezpečnostním pokynům. Užijte si zkušenosti s MAXIMA Grooved Receiver Line Quick Detach Ruger Rings a vždy dbejte na bezpečnost při používání vaší pušky.